




EXPANDED METAL

Available in Stainless Steel, Galvanized and Aluminum.



Regular Expanded Metal • Carbon Steel - ASTM A569/569M


Style	Wgt. in lbs. Per C.S.F.		Center to Center		Size of Opening		Size of Strands		
	Plain	Galv.	(A) Width	(B) Length	(C) Width	(D) Length	(E) Width	(F) Thk.	
1/4"	#18	114	171	0.255	1.00	0.172	0.719	0.073	0.048
1/2"	#18	70	85	0.500	1.20	0.438	0.938	0.088	0.048
	#13	147	173	0.500	1.20	0.313	0.938	0.096	0.092
3/4"	#16	54	65	0.923	2.00	0.813	1.750	0.099	0.060
	#13	80	92	0.923	2.00	0.750	1.688	0.096	0.092
	#9	180	195	0.923	2.00	0.688	1.563	0.148	0.134
1"	#16	44	51	1.090	2.40	1.000	2.063	0.096	0.060
1 1/2"	#13	60	68	1.330	3.00	1.188	2.500	0.104	0.092
	#9	120	131	1.330	3.00	1.125	2.375	0.142	0.135
	#6	250	273	1.330	3.00	1.000	2.313	0.201	0.198

Continued on next page

Free delivery in Houston with a minimum order.




713.672.7595
800.839.4766
Fax 713.672.0653
texasironandmetal.com



Flattened Expanded Metal • Carbon Steel - ASTM A569/569M

Style	Wgt. in lbs. Per C.S.F.		Center to Center		Size of Opening		Size of Strands		
	Plain	Galv.	(A) Width	(B) Length	(C) Width	(D) Length	(E) Width	(F) Thk.	
1/4"	#18	111	165	0.255	1.03	0.094	0.688	0.086	0.040
1/2"	#18	66	88	0.500	1.26	0.281	1.000	0.109	0.039
	#13	140	162	0.500	1.26	0.250	1.000	0.122	0.070
3/4"	#16	51	61	0.923	2.10	0.750	1.750	0.115	0.048
	#13	75	86	0.923	2.10	0.688	1.782	0.119	0.070
	#9	171	186	0.923	2.10	0.563	1.688	0.164	0.120
1"	#16	41	50	1.090	2.56	0.875	2.250	0.115	0.048
1 1/2"	#13	57	68	1.330	3.20	1.063	2.750	0.138	0.070
	#9	111	128	1.330	3.20	1.000	2.563	0.175	0.110
	#6	221	267	1.330	3.20	1.000	2.563	0.195	0.170



Expanded Metal Grating • Carbon Steel - ASTM A569/569M

Style	Wgt. in lbs. Per C.S.F.		Center to Center		Size of Opening		Size of Strands	
	Plain	Galv.	(A) Width	(B) Length	(C) Width	(D) Length	(E) Width	(F) Thk.
3.00 #	300	320	1.333	5.33	0.938	3.438	0.261	0.183
3.14 #	314	334	2.000	6.00	1.625	4.875	0.308	0.250

Continued on next page

Carbon • Stainless • Alloy • Aluminum
texasironandmetal.com

Expanded Metal Grating • Carbon Steel - ASTM A569/569M (cont.)

Style	Wgt. in lbs. Per C.S.F.		Center to Center		Size of Opening		Size of Strands	
	<i>Plain</i>	<i>Galv.</i>	(A) <i>Width</i>	(B) <i>Length</i>	(C) <i>Width</i>	(D) <i>Length</i>	(E) <i>Width</i>	(F) <i>Thk.</i>
4.00 #	400	430	1.333	5.33	0.938	3.438	0.297	0.215
4.27 #	427	457	1.412	4.00	1.000	2.875	0.297	0.250
5.00 #	500	550	1.333	5.33	0.813	3.375	0.327	0.250
6.25 #	625	685	1.412	5.33	0.813	3.375	0.347	0.312
7.00 #	700	750	1.412	5.33	0.813	3.375	0.388	0.312



**TEXAS IRON
& METAL**

SUPPLY ON DEMAND.

713.672.7595

800.839.4766

Fax 713.672.0653

texasironandmetal.com